


**LED DIGITAL LAMP (SIGNAGE)**  
**CAPTURE YOUR CLIENTS' ATTENTION.**  
**REEL THEM IN.**



**ECONOMICAL**  
Reduced marketing expenses thanks to the low cost production of unlimited content displayed. Optimize message performance with the tap of a finger.



**EFFICIENT**  
Optimal return on investment with the ability to rapidly see the results of an effective marketing strategy. With digital signage, your messages will have a greater impact than ever before.



**ATTRACTIVE AND APPEALING**  
Powerful, responsive communication made possible through real-time broadcasting of messages.



**SIMPLE, FLEXIBLE BROADCASTING**  
Nummax Manager, our content management software, allows you to schedule your content displayed from a distance in a matter of minutes. With dynamic messaging, pre-program content display times weeks in advance.

## TECHNICAL SPECIFICATIONS

Model	LED Ring
Display Area (WxH)	1920 x 240 mm 75,6 x 9,44 in
Total dimensions (including frame) (Diam xH)	diam 615 x 240 mm 24,21 x 9,44 in
Stackable	No
LED spacing	2,5mm
LED configuration	SMD
Pixel resolution (px)	768 x96
Colour capacity	16 bits
Brightness	1500 nits
Light and Temperature sensor	No
LED display dimming	No
Refresh rate	2000 Hz+
Frequency	60 Hz+
Colour type	RGB
Viewing distance	2 m
Viewing angle	H140°, V120°
Lifetime	100 000H+

Power	AC-110-240V
Warranty (parts & labour)	3 years
Compliance	c ETL us
Maximum power consumption	368w
Average power consumption	147w
Working temperature	-5/60 °C
Working humidity	10-80%
Working environment	Interior
Frame	Iron
Weight	50 lbs
Orientation	Landscape
Frame installation	Hanging
Player	Included
Software	Included
Communication	Wired or wifi
Speaker(s)	Option

