

LED Miami Signs / 305-328-9557
www.ledmiamisigns.com

Outdoor Digital Display

LMS Series Pitch 10MM / 3.14' x 3.14'



Characteristics

- High Resolution P10mm RGB
- LEDs Screens are Fabricated with the Highest Level of Technology
- Cabinet 960 x 960 x 150mm
- Protection IP65 (Front) & IP54 (Rear)
- Cabinet Weight 100lbs
- Easy To Use Program for Distribution of content
- Brightness **9,500 Nits**
- **MAX** Consumption 450W

Specifications

Pixel Configuration	1 Red, 1 Green, 1 Blue
Pixel Density	10,000 Pixel/m ²
Diode Density	15,624 Pixel/m ²
Brightness	9,500 Nits
Viewing Angel	120° (+/- 70°) Horizontal 60° (+/- 32.5°) Vertical
LED Life Span	100,000 Hours by 50% Brightness
Video Processing	16 Bit, 100% Digital
Processing Color	16 Bit Per Color
Colors	18 Quadrillion
Color Wavelength	Red: 1600nm, Green: 3300nm, Blue: 700nm

Color Temperature	6,000 - 12,000k (Adjustable)
Module Configuration	24 x 24 Matrix 240 x 240 mm
Cabinet Configurations in Pixels	96 x 96
Voltage	120/240 Volts, 50/60 Hz
Cabinet Weight	100lbs
Software	NovaStar
Refresh Rate	1,920HZ
Warranty	3-Year
Working Temperature	(-34°C a 50°C)
Cabinet Materials	Steel
Degree of Protection	IP65 (Front) & IP54 (Rear)

